

Veradel® A-704P

polyethersulfone

Veradel® A-704P (PESU) is a powder designed for dissolving or dispersing into solutions. It can also be ground to smaller particle size, or blended with other solid particles.

PESU offers excellent toughness and outstanding hydrolytic resistance. It resists attack from steam, boiling water and mineral acids. Cast films or coatings of PESU are transparent and have additional desirable properties including long term thermal stability, excellent metal adhesion and formability and inherent flame resistance.

Typical applications include high-temperature coating formulations, advanced high-temperature composites and specialty adhesives.

Veradel® A-704P is relatively low in molecular weight and viscosity. A higher molecular weight and viscosity grade is available as A-304P.

This grade was formerly marketed as Radel® A PESU

• Natural: Veradel® A-704P NT

General				
Material Status	 Commercial: Active 			
Availability	 Africa & Middle East Asia Pacific Europe		Latin AmericaNorth America	
Features	 Acid Resistant Chemical Resistant Creep Resistant Flame Retardant Food Contact Acceptable Good Adhesion Good Dimensional Stabil Good Thermal Stability 	 High Flow High Heat High Tens Hydrolysis Low Molect 	 Good Toughness High Flow High Heat Resistance High Tensile Strength Hydrolysis Resistant Low Molecular Weight Medium Rigidity 	
Uses	 Adhesives 	 Coating A 	 Coating Applications 	
RoHS Compliance	 RoHS Compliant 			
Appearance	 Transparent - Slight Yello 	W		
Forms	 Powder 			
Processing Method	CoatingSolution Processing	• Spraying		
Physical		Typical Value Unit	Test method	
Density / Specific Gravity		1.37	ASTM D792	
Water Absorption (24 hr)		0.60 %	ASTM D570	
Residual Solvent		0.50 %	Internal Method	
Viscosity - Solution 1 (40°C)		200 mPa·s	Internal Method	
Thermal		Typical Value Unit	Test method	
Glass Transition Temperature		220 °C	ASTM E1356	
CLTE - Flow		4.9E-5 cm/cm	∕°C ASTM D696	

Veradel® A-704P

polyethersulfone

Notes

Typical properties: these are not to be construed as specifications.

¹ 25% in Dimethylacetamide

Veradel® A-704P polyethersulfone

www.syensqo.com

Safety Data Sheets (SDS) are available by emailing us or contacting your sales representative. Always consult the appropriate SDS before using any of our products.

Neither Syensqo nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Syensqo's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Syensqo's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right.

All trademarks and registered trademarks are property of the companies that comprise the Syensqo or their respective owners.

© 2024 2023 Syensqo. All rights reserved.

